



SUNNY BEAM with *Bluetooth*[®]



- Wireless communication via *Bluetooth*[®]
- Monitors up to 12 Sunny Boy inverters
- 100 day data storage
- Audio alarm
- Key performance data at a glance
- Easy-to-read LCD graphic display
- Integrated solar cell
- USB ready
- Desktop or wall-mount

SUNNY BEAM with *Bluetooth*[®] Wireless Technology

Wireless system performance monitoring for Sunny Boys


The new Sunny Beam represents the ultimate in wireless system performance monitoring. Completely updated, the Sunny Beam now features *Bluetooth*[®] wireless technology for improved performance and versatility. It communicates with up to 12 Sunny Boy inverters and graphically displays all of the key performance data of your solar system. It also automatically records and stores system information for the last 100 days. Setup is quick and easy via an intuitive interface and menu system. Its sleek design makes the Sunny Beam a welcome addition to any home or office, with system performance available at a glance—wirelessly.

Technical Data

| | SUNNY BEAM with Bluetooth® |
|---|--|
| Inverter communication | Bluetooth® |
| PC communication | USB 2.0 |
| Maximum number of Sunny Boy inverters monitored | 12 |
| Maximum unobstructed communication range (US series Sunny Boy inverter) | 150 ft. |
| Power supply | Integrated solar cell, USB cable, internal batteries |
| Number of batteries | 2 |
| Type of battery | NiMH (1.2 V) with low self-discharge |
| Ambient temperature | 32 to 104 °F |
| Protection rating | IP20 |
| Dimensions: W x H x D in inches | 5.0 x 3.0 x 7.6 |
| Weight | approx. 0.77 lbs (with batteries) |
| Language versions - software / manual | German, English, French, Italian, Dutch, Portuguese, Spanish, Czech |
| Display | LCD display |
| Operation | Rotary push button |
| Warranty | 5 years |
| Certificates and approvals | Visit www.SMA.de |
| General information displayed | Time, date |
| System data displayed | Current performance, daily yield, total yield, annual yield, CO ₂ savings, earnings |
| USB cable | ● |
| USB plug-in power supply | ○ |
| Replacement batteries | ○ |
| SMA Bluetooth® repeater | ○ |
| ● Standard equipment ○ Optional | |



Wireless **communication** with the inverters via Bluetooth®



Large, easy to read **LCD display**



Audio alarm




USB port for data transfer to a PC and charging the internal batteries



Single button provides intuitive scroll and select navigation



Power supply via **solar cell** and rechargeable battery



Compact and light
Dimensions: 5.0 x 3.0 x 7.6 in
Weight: 0.77 lbs

SBEAMBT-DUS0940 18 SMA and Sunny Beam are registered trademarks of SMA Solar Technology AG. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. Text and illustrations conform to technical standards on printing. Technical modifications reserved. No liability for printing errors. Printed on chlorine-free paper.