

TRANSFORMERLESS
STRING INVERTERS**PVI 3800TL**
PVI 5200TL
PVI 6600TL
PVI 7600TL**FEATURES**

- 600 VDC
- Highest industry peak and CEC efficiencies
- Lightweight, compact design - smallest in the industry
- Quick and easy installation
- Wide operating voltage range
- DC disconnect

OPTIONS

- Web-based monitoring
- Revenue grade monitoring
- DC arc-fault detection and interrupt



TRANSFORMERLESS STRING INVERTERS

Solectria Renewables' PVI 3800TL, 5200TL, 6600TL and 7600TL are compact, transformerless, single-phase inverters with the highest peak and CEC efficiencies in the industry. These inverters come standard with an integrated DC disconnect, optional DC arc-fault detection and interrupt, 1 or 2 MPP tracker(s), and a user-interactive LCD and keypad. Its small and lightweight design make for quick and easy installation and maintenance. These inverters include an enhanced DSP control, comprehensive protection functions, and advanced thermal design enabling highest reliability and uptime. They also come with a standard 10 year warranty with options for 15 and 20 years.



Built for the real world

COMING SOON

SPECIFICATIONS	PVI 3800TL	PVI 5200TL	PVI 6600TL	PVI 7600TL
DC Input				
Absolute Maximum Open Circuit Voltage		600 VDC		
Operating Voltage Range		120-550 VDC		
MPPT Input Voltage Range		200-500 VDC		
MPP Trackers	1	2		
Maximum Operating Input Current	20 A	15 A per MPP tracker	18 A per MPP tracker	20 A per MPP tracker
AC Output				
Nominal Output Voltage		208 or 240 VAC, 1-Ph		
AC Voltage Range		-12%/+10%		
Continuous Output Power	208 VAC	3300 W	5200 W	6600 W
	240 VAC	3800 W	5200 W	7600 W
Continuous Output Current	208 VAC	15.8 A	25 A	31.7 A
	240 VAC	15.8 A	21.6 A	31.7 A
Maximum Backfeed Current		0 A		
Nominal Output Frequency		60 Hz		
Output Frequency Range		59.3-60.5 Hz		
Power Factor		Unity, > 0.99		
Total Harmonic Distortion (THD)		< 3%		
Efficiency				
Peak Efficiency		98%		
CEC Efficiency		97.5%		
Tare Loss		<1 W		
Temperature				
Ambient Temperature Range (full power)		-13°F to +122°F (-25°C to +50°C)		
Storage Temperature Range		-40°F to +185°F (-40°C to +85°C)		
Relative Humidity (non-condensing)		0-100%		
Data Monitoring				
Optional SolrenView Web-based Monitoring		External		
Optional Revenue Grade Monitoring		External		
External Communication Interface		RS485		
Testing & Certifications				
Safety Listings & Certifications		UL 1741/IEEE 1547, UL1699B, CSA C22.2#107.1, FCC part 15 A&B		
Testing Agency	ETL	CSA		
Warranty				
Standard		10 year		
Optional		15, 20; extended service agreement		
Enclosure				
DC Disconnect		Standard, fully-integrated		
Dimensions (H x W x D)	17.5 x 15.8 x 8.5 in. (445 x 401 x 216 mm)	26.8 x 15.8 x 8.5 in. (680 x 401 x 216 mm)		
Weight	43 lbs (19.5 kg)	65 lbs (29.5 kg)		
Enclosure Rating		Type 4		
Enclosure Finish		Aluminum		

Copyright © Solectria Renewables, LLC. All information subject to change without notice. February 2014 DOCK-070356-B

